

## Einbauanleitung für: MG MIDGET MK III 1966-69 MG MIDGET MK III 1974-79

Das Windschott besteht aus folgenden Teilen:

1. Scheibe mit Leiste und Vorhang
2. Befestigungselementen
3. Einsteckplatte
4. Riemchen
5. Kugelkopfschrauben
6. Hülle für Scheibe

### Montage:

- Verdeck öffnen.
- Die Befestigungselemente (2) links und rechts in die Schlitzze der Verstärkungsleiste (1) stecken.
- Links und rechts befinden sich die Befestigungen des Verdeckgestänges.
- Die Schrauben heraus drehen und mit dem gleichen Schrauben L + R die Einsteckplatte befestigen.
- Nun wird die Scheibe mit den Befestigungselementen (2) in der Schlitzze der Einsteckplatte eingeführt. Als Abschluss wird der Mittelpunkt des Kugelkopfes (5) für das Riemchen (4) an der L+R Seitenverkleidung angezeichnet. Mit 2.5mm Bohrer vorbohren, die Kugelköpfe für den Vorhang befestigen.
- Die Schutzfolie ist von der Scheibe zu entfernen.
- Beim geschlossenem Verdeck kann das Windschott im Fahrzeug verbleiben.
- Beim lagern der Scheibe die Hülle benutzen.

**Hinweis:** Verwenden Sie zum Reinigen des Schildes immer feuchte Tücher.

## Fitting instructions for: MG Midget MK III 1966-69 MG Midget MK III and midget 1974-79

The windstop consists of the following parts:

1. Shield (Polycarbonate) with frame and skirt
2. Right and left fastening brackets
3. 2 Insert plate
4. Straps with tenax
5. Securing pins
6. Storage bag

### Fitting:

- Open the hoodcover.
- Push fastening brackets (2) into the left and right side of the frame (1).
- Remove the pins that attach the hoodframe. First the left side, install the insert plate (3) in front of the plate which you have just removed and refasten, using the screws that you have removed. Do the same with the right side.
- Push the frame with shield and skirt (1) with the other side of the fastening brackets (2) into the insert-plates (3).
- Press fastening brackets (2) firmly and pull down the straps (4) and mark position for the securing pins (5).
- Drill whole 2,5mm and fit the securing pins (5).
- Remove the foil from the shield.
- The windstop can stay in the car when the hood is closed.

**NOTE:** Always use wet clothes to clean shield.

